




TECHNICAL INFORMATION



Example of stones

Indicative composition of stones on the layer

name	layout dimensions (mm)			number of pieces on one layer	quantity (m ²)		weight (kg)			max. tonnage up to 24 t		note
	height	length	width		layer	pallet	layer	pallet	pallet included	pcs of pallets	m ²	
BEST ESMERO 	60	-	-	104	0.70	8.40	90	1080	1110	21	176.40	1 pallet = 12 layers

We are holders of the Gold Certificate for complete certification according to ISO 9001, ISO 14001, ISO 50001, ISO 45001. Our products are manufactured and inspected pursuant to European harmonized standards.

product height	production standard	maximum deviation from declared production dimensions		transverse tensile strength	skid/slip resistance	ČSN 73 1326, weather resistance, method A
		width and length	height			
60 mm	ČSN EN 1338	±3 mm	±2 mm	≥ 3.6 MPa	satisfactory	≤ 1.0 kg/m ² after 100 cycles

EXPLANATIONS OF PICTOGRAMS



Paving intended for sidewalks, bicycle paths, parking spaces and movement of motor vehicles up to 3.5 t.



Surface Metropol




No facet

SURFACE FINISHES AND COLOURS



ANTHRACITE



NATURAL



WHITE

surface	characteristics	colour
METROPOL	blast-treated surface, produced according to a special recipe using coloured grits	anthracite, natural, white

GENERAL INFORMATION

Two-layer vibrated paving with high strength, frost resistance, surface resistance to water and chemical de-icing agents. The paving has low abrasion and good adhesion properties. BEST concrete elements are permanently impregnated against contamination.

The minimum shipping quantity is 1 layer; the stones cannot be delivered individually and it is not possible to determine the ratio of stones in the composition. The goods are loaded on marked pallets BEST (30 kg) or BEST large (38 kg) according to the production capacity of individual plants.

When laying, it is important to follow the correct procedure according to the instructions for use (www.best.cz). The individual stones are placed randomly, creating a surface with irregular joints. Due to the special paving method, when ordering this paving, it is necessary to take into account the use of approximately 10-20 % less paving than the actual paved area.

Caution: BEST ESMERO paving must be compacted with a vibrating plate with a plastic pad weighing no more than 100-130 kg with a set centrifugal force of 18-20 kN.

