


TECHNICAL INFORMATION



Layout dimensions

name		layout dimensions (mm)			quantity (pcs)		weight (kg)			max. tonnage up to 24 tonnes	
		height	length	width	layer	pallet	pcs	pallet	pallet included	pcs of pallets	pcs
BEST RONDA		300/220	500	300	4	12	90	1080	1110	21	252
BEST RONDA R0.5 outer		300/220	length of outer curve 780	300	3	9	97	873	903	24	216
BEST RONDA R1 outer		300/220		300	3	9	119	1071	1101	21	189
BEST RONDA R16 outer		300/220		300	3	9	140	1260	1290	18	162

We are holders of the Gold Certificate for complete certification according to ISO 9001, ISO 14001, ISO 50001, ISO 45001. Our products are manufactured and inspected pursuant to European harmonized standards.

product height	product width	production standard	maximum deviation from declared production dimensions		bending tensile strength	skid/slip resistance	ČSN 73 1326, weather resistance, method A
			width and height	length			
300 mm	300 mm	ČSN EN 1340	±3 % (min. 3 mm, max. 5 mm)	max. ±1 %	≥ 3.5 MPa	satisfactory	≤ 1.0 kg/m ² after 100 cycles

EXPLANATIONS OF PICTOGRAMS




Road curb



Surface basic

SURFACE FINISHES AND COLOURS



NATURAL

surface	characteristics	colour
STANDARD	standard surface with natural aggregate roughness corresponding to the visible layer of concrete paving	natural

GENERAL INFORMATION

Two-layer vibrated curb with high strength, frost resistance, surface resistance to water and chemical de-icing agents. The curb has low abrasion and good adhesion properties. BEST concrete elements are permanently impregnated against contamination.

The minimum shipping quantity is 1 piece. The goods are loaded on marked pallets BEST (30 kg) or BEST large (38 kg) according to the production capacity of individual plants.

When laying, it is important to follow the correct procedure according to the instructions for use (www.best.cz).

Use: BEST RONDA road curbs are suitable for the edges of traffic areas, especially for creating roundabouts.

